

AH-02120

Agent Releasing Control Panel



Characteristics

- This compact and esthetic unit is ideally suited for variety of agent releasing applications such as FM-200, CO2, Dry & Wet Chemical.
- Expansion is available in order to protect more areas.
- Auto and Manual operation for agent releasing.
- System enables highly reliable monitoring and suppression control for up to eight separate hazards.
- Audible and visible indication when system has fault condition.
- Digital Release Countdown.

Optional Features

- 24 Characters LCD Display with 255 Event History Log.
- Printer (built into front door).
- Single-tone Voice PA System.
- Multi-tone Voice PA System.
- Special case design includes agent tank with control unit.

Specification

Model	AH-02120
Power	220V AC/50HZ *Others also available
Battery Capacity	24V DC 4Ah
Zone Voltage	24V DC
EOL Resistance	10kΩ
Detection Type	Cross-zone detection
# of heat detectors connected	No limit *Except electronic-type
# of smoke detectors connected	30/zone *Horing Lih manufactured
Dimensions	520mm(H) x 390mm(W) x 135mm(D) 1000mm(H) x 500mm(W) x 175mm(D)
Color	Ivory

Accessories Specification

Electromagnetic Valve	24VDC
Sounder	24VDC 200mA
Releasing Indicator	24VDC 200mA
Manual Pull Station	Up to 10/zone via RS 485