

Rate of Rise Heat Detector



AHR-871

Characteristics

- Heat-sensing diaphragm can operate for unlimited number of times and is not affected by room temperature. The conducting parts use gold coating to avoid oxidation.
- Uses glass tube to avoid humidity and stabilize the ventilation function. Glass tube also can expel non-fire heat to avoid false alarms.
- The unit is completely sealed; its function is not affected by humidity, dust or insects.
- This detector has passed strict quality control through automatic repetitive testing and been calibrated automatically under stable temperature and humidity conditions. Thus, quality and reliability are consistent from the first detector produced to millionth.

Specifications

Model	AHR-871		
Type	2-wire	3-wire	4-wire
Alarm Contact	N/A	N/A	0.8A @30V DC 0.4A @125V AC
Voltage Range		12~30V DC	
Alarm Current @24V DC 470Ω	40 mA	40 mA	35 mA
Alarm Temperature		Comply to EN54	
Ambient Temperature		0°C ~+55°C	
Material		Fire-proof plastic	
Dimensions		111mm(Dia.) x 45mm(H)	
Weight		About 130g	
Color		White	

Effective Alert Area

Construction/Height	Under 4M	4M ~ 8M
Fire-proof Building	90 M ²	45 M ²
Ordinary Building	50 M ²	30 M ²