CEMEN FIRE ALARM SYSTEM

LPCB ISO 9001 | Model AH-9717
Manufactured :
HORING LIH INDUSTRIAL CO.,LTD.
MADE IN TAIWAN
CE

FIRE ALARM EQUIPMENT

Manual Station

S-336   S-336 with base

Features

- Emergency press alarm, immediately activates fire alarm signal.

- Indicator Light above fire alarm push-button confirms the alarm signal transfer.

- There are a phone jack and reset buttton behind the cover cap.

- Type I is simultaneous dual loop, Type II is simultaneous duel signal transfer

✱ Optional base is available.(S-336 with base)

Specification

Model	S-336	S-336 With base
Operating Power	24VDC 30mA	
Operating Contact	Max.30VDC 500mA	
Sub-function	Phone Jack, confirmation LED, reset button	
Material	Fire-proof plastic	
Dimensions	140mm(Dia.) x 45mm(H)	140mm(Dia.) x 65mm(H)
Weight	160g	300g

Diagram

Type I
A
L (Z+)
Lc (Z-)
T
Tc

A : Transmitting
L,LC : Loop & Com
T,Tc : Telephone & Com

Type II
A
L (Z+)
Lc (Z-)
T
Tc
B

220V AC 0.4A
24V DC 0.8A